

# POS Printer RP80

<b>Item #</b>	<b>Thermal Printer RP80</b>	
<b>Photo</b>		
<b>Color</b>	<b>Black</b>	
<b>Price (FOB)</b>	<b>RP80USE(USB+Serial+Ethernet)</b>	
	<b>RP80US(USB+Serial), RP80UP(USB+Parallel)</b>	
<b>Print</b>	Printing Method	Thermal Line
	Printing Speed	250mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
<b>Character</b>	Character Set	ANK,GB18030(Chinese)
	Print Font	ANK: 12 x24,9x17, Chinese: 24 x 24
	Character per Line	48-font A/64-font B
<b>Paper Spec</b>	Paper Type	Thermal paper
	Paper Width	79.5± 0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06 to 0.07mm
<b>Paper Supply Method</b>	Drop-in paper load	
<b>Reliability</b>	MCBF	60 million lines
	Auto Cutter	500,000 cuts
	TPH	100km
<b>Barcodes</b>	UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93,	
<b>Emulation</b>	ESC/POS	
<b>Driver</b>	Windows2000/XP/7/VISTA	
<b>Sensor</b>	Paper Near End Sensor, Paper End Sensor	
<b>Drawer Port</b>	1 Port	
<b>Interface</b>	RS-232, Parallel, USB, Ethernet	
<b>Power Supply (Adapter)</b>	AC100 ~240V(± 10%) DC 24V, 2A	
<b>Auto cutter</b>	Type	Guillotine
	Life	1,000,000 cuts
<b>Physical</b>	Net Weight	1.3kg
	Gross Weight	2.8kg
	Printer Dimension (WxLxH)	145 x 195x 148 mm
<b>Application</b>	Restaurants, Department Stores, Kitchen, Convenience Stores, Specialty Retail, Super market	